



PATIENT SAFETY 4.0

hd260/270/470MS

hd260/270/470MS



hd 260/270/470 MS

The impulse sealers hd 260 MS, hd 270 MS and hd 470 MS are our most economical bar sealers for the packaging of sealable pouches and reels as well as thermoplastic film. Thanks to the adjustable sealing timer the devices can be easily adapted to the material. They are ideally suited for use in smaller institutions and tattoo studios.



COMPACT DESIGN.

The hd 260 MS, hd 270 MS and hd 470 MS are equipped with an integrated roll holder and manual cutting device.

OPERATION.

The timer is easy adjustable to the corresponding material. After the sterilisation packaging has been inserted, the sealing process is started by pushing down the hand lever. During the impulse sealing process the film can be cut with the manual cutting device. Once the sealing time has elapsed, a signal sounds to complete the sealing process.



FLEXIBILITY.

The sealers are suitable for packaging sealable paper bags (EN ISO 11607-1/ EN 868-4), sealable pouches and reels (EN ISO 11607-1/EN 868-5) made of film and paper according to the EN 868-3 and for hot air sterilization film on request. The cutting width of hd 260 MS and hd 270 MS is 250 mm (9.8 inch) and of the hd 470 MS even 450 mm (17.7 inch).

SEAL STRENGTH.

The sealing seams of 8 mm (0.3 in) have a high seal strength but also excellent peeling properties without paper shredding, even if the user peels the pack open in the wrong direction.

SUSTAINABILITY.

Wearing parts can be easily replaced by the user if necessary. The need of wearing parts is very low and it is not necessary to exchange expensive modules. Thanks to the impulse sealing system there is no heat up time. The hd 260 MS has no energy consumption when not in use, the hd 270 MS and hd 470 MS only for the digital display.



InkTest PRO

The InkTest PRO is an innovative test system and an easy, cost-efficient way for routine testing of the sealing seams. Any irregularities that occur (e.g. channels) become visible immediately after the single-use cartridge is pressed on. No pipettes or other tools are needed to fill it. There is no danger of the test liquid dripping or transferring onto other objects on your workstation or your clothes and skin. The hawo InkTest comes in packaging designed especially for ease of use (30 pcs.) with the aluminium packaging ensuring that the ink is protected from sunlight.



Seal Check dent

The Seal Check indicator makes defective areas of the sealing seam visible on the dark indicator strip. The hawo Seal Check dent comes in a package designed especially for ease of use (100 pcs.) and with a reference card for assessing the results.



	hd 260 MS	hd 270 MS	hd 470 MS
RANGE OF USE			
Especially suitable for use in medical practice and tattoo studios	Х	X	X
SEALING MATERIALS			
Sealable paper pouches according to EN ISO 11607-1/EN 868-4	x	x	х
Sealable pouches and reels according to EN ISO 11607-1/EN 868-5 made of film and paper according to EN 868-31	х	Х	X
Hot air sterilization film	on demand	х	×
TECHNICAL DATA			
Mains connection	115/230 V	115/230 V	115/230 V
Mains frequency	50/60 Hz	50/60 Hz	50/60 Hz
Power consumption max. (only during sealing process)	870 VA	870 VA	870 VA
Dimensions W x D x H	400 x 310 x 220 mm (15.7 x 12.2 x 8.7 inch)	400 x 310 x 220 mm (15.7 x 12.2 x 8.7 inch)	555 x 310 x 220 mm (21.9 x 12.2 x 8.7 inch)
Stainless steel AISI 304 casing cover	X	X	X
Weight	8.5 kg (18.7 lbs.)	8.5 kg (18.7 lbs.)	11 kg (24.2 lbs.)
Impulse Sealing system	X	Х	x
Sealing seam width	8 mm	8 mm	8 mm
Sealing seam length	250 mm (9.8 inch)	250 mm (9.8 inch)	450 mm (17.7 inch)
Integrated roll holder	Х	X	X
Integrated cutting device	X	X	X
Cutting width	250 mm (9.8 inch)	250 mm (9.8 inch)	450 mm (17.7 inch)
Microprocessor control	X	X	X
Display		7-segment-display	7-segment-display
Piece counter		X	X
ACCESSORIES			
Storage tray	x	Х	X
InkTest / InkTest PRO (dye penetration test)	Х	Х	Χ
Seal Check	x	х	х

¹ Not suitable for gusseted pouches and reels.

Technical modifications reserved 05/2021 | 9.343.039





hawo GmbH Obere Au 2-4 74847 Obrigheim Germany T +49 (0) 6261/9770-0

F+49 (0) 6261/9770-69

info@hawo.com www.hawo.com hawo USA: hawo

150 North Michigan Avenue 35th Floor

Chicago. Illinois 60601 T +1 312 585 8329 F +1 312 644 0738 info@hawo-usa.com www.hawo-usa.com

hawo ASIA: hawo 25 International Business Park #03-105 German Centre Singapore 609916 T +65 6433 5339 F +65 6433 5359 info@hawo-asia.com www.hawo-asia.com

Follow us:









LABORATORY EQUIPMENT MAINTENANCE, REPAIR, CALIBRATION AND SALES

Established in 1987, Henderson Biomedical is the UK's leading laboratory equipment sales and service provider. Our knowledgeable team can provide you with excellent sales advice on a range of different types of laboratory equipment including centrifuges, refrigerators, freezers and heat sealers.

Henderson Biomedical is also able to provide you with first class after-sales service and calibration of your laboratory equipment. We are an **ISO 17025 (UKAS) accredited calibration test laboratory** and our team of Field Service Engineers cover the whole of the United Kingdom.

Please contact us for more information on the types of equipment we supply and the different after-sales services we can offer.

Henderson Biomedical

Unit 3, Swan Close Croydon CRO 2DZ United Kingdom

Tel: 020 8663 4610

