



ULT-91i

ULT TECHNICAL SPECIFICATIONS

Multi voltage.



DIMENSIONS		VALUE
Dimension HxWxD (D incl. handle)		836x947x720 (790)
Dimension inner HxWxD		310x640x445
Weight Gross/Net, kg		137 / 102
Package weight		35
Packaging dimensions HxWxD		1011x1019x824
Material inner cabinet		Stainless steel
Material outer cabinet		Painted Steel
Insulation type		Polyurethane with Cyclopentane
Insulation thickness		120
Type of packaging		Cardboard, EPS, PE, wood
Mobility		3 x adjustable feet, 3 x castors
FEATURES		VALUE
Lock		<input checked="" type="checkbox"/>
LED light		<input type="checkbox"/>
Battery backup		<input checked="" type="checkbox"/>
Porthole		<input checked="" type="checkbox"/>
Porthole size		20 mm
Dry contact		<input checked="" type="checkbox"/>
Door reversibility		<input type="checkbox"/>
Vacuum valve		<input checked="" type="checkbox"/>
VIP (Vacuum Insulated Panel)		<input checked="" type="checkbox"/>
STORAGE		VALUE
Capacity (L)		88
ALARMS		VALUE
High / Low temperature		<input checked="" type="checkbox"/>
Open door		<input checked="" type="checkbox"/>
Power failure		<input checked="" type="checkbox"/>
Probe failure		<input checked="" type="checkbox"/>
COOLING		VALUE
Refrigerant		Nature R
Noise		< 48
Voltage		230V
Frequenze		50/60 Hz
Temperature range		-20 / -86
Ambient condition		25 °C



ULT-91i

ULT TECHNICAL SPECIFICATIONS

Multi voltage.

BIOMEDICAL

OPERATING CONDITIONS		
Voltage/Frequency	Voltage/Hz	230V, 50/60Hz
Max Ambient	°C	43
Max Humidity	% rh	65
PERFORMANCE		
PERFORMANCE	UNIT	VALUE
All data in RT25°C		
Temperature Range	°C	-20 to -86
Uniformity in performance - difference between top and bottom	°C	+/- 2,5
Pull down time	Minutes	103 min. to -75°C
Hold over time	Minutes	N/A
Noise	dB	< 48
Energy Consumption, kWh / 24h	kWh/24h	5,22 kWh/24h set -80°C
Energy year	kWh/year	1905kWh/y set -80°C
Instant Power Consumption	kW	PD 0,650/Stable 0,280
Heat Rejection	W	N/A
U-Value	W/m ² K	N/A
COOLING COMPONENTS		
		VALUE
Refrigerant/Amount (gram)		Nature R 2/149gr
Number of compressors	pcs	1
Varibel speed compressor	Yes/No	Yes
Internal air distribution (type of)		Static
Evaporator Fan	Yes/No/Variable	No
Condenser Fan	Yes/No/Variable	Yes
Number of probes	pcs	2
Defrost	Yes/No	No
CONTROLLER		
		VALUE
Controller	y/n/optional	yes
Controller type		i-Care touch
USB Connection	y/n	yes
Data connection	USB	yes
Controller abilities		logging of data & alarms
Controller languages		EN, DE, FR
Temperature curve in controller	y/n	yes



LABORATORY EQUIPMENT MAINTENANCE, REPAIR, CALIBRATION AND SALES

Established in 1987, Henderson Biomedical is the UK's leading laboratory equipment sales and service provider. Our knowledgeable team can provide you with excellent sales advice on a range of different types of laboratory equipment including centrifuges, refrigerators, freezers and heat sealers.

Henderson Biomedical is also able to provide you with first class after-sales service and calibration of your laboratory equipment. We are an **ISO 17025 (UKAS) accredited calibration test laboratory** and our team of Field Service Engineers cover the whole of the United Kingdom.

Please contact us for more information on the types of equipment we supply and the different after-sales services we can offer.

Henderson Biomedical

Unit 3, Swan Close
Croydon CR0 2DZ
United Kingdom

Tel: 020 8663 4610

**For sales enquiries: sales@henderson-biomedical.co.uk
For all other enquiries: info@henderson-biomedical.co.uk
www.henderson-biomedical.co.uk**

