



ULTF 700

ULT TECHNICAL SPECIFICATIONS



-40°C
-90°C

Product Type		ULT (230V)
Color code handle / Color code housing		RAL 9003 / RAL 9003
MEASURES		
Interior volume [L]		700
Net weight of the unit (empty) [kg]		289
Permitted load [kg]		200
Permitted load of individual compartment (kg)		50
Wall clearance back [mm]		100
Wall clearance sidewise [mm]		250
Mobility		4 wheels, 2 w. lock
INTERNAL DIMENSIONS		
Interior width [mm]		890
Interior height [mm]		1300
Interior depth [mm]		605
DOORS		
Inner doors		2
Unit doors		1
HOUSING DIMENSIONS NOT INCL. FITTINGS AND CONNECTIONS		
Width net [mm]		1110
Height net [mm]		1966
Depth net [mm]		938
PERFORMANCE DATA TEMPERATURE		
Temperature range [°C]		-90...-40
Temperature variation at -80 °C [± K]		2.5
Temperature fluctuation at -80 °C [± K]		1.5
Cooling down time (min) from 22 °C to -80 °C		450
Warm-up time during power failure from -80 °C / -122 °F to -60 °C / -76 °F [min]		250
ELECTRICAL DATA		
Rated Voltage [V]		230
Power frequency [Hz]		50
Nominal power [kW]		1.6
Unit fuse [A]		10
Power plug standard		2m C13 CEE 7/7
Phase (Nominal voltage)		1~



ULTF 700

ULT TECHNICAL SPECIFICATIONS

ENVIRONMENT SPECIFIC DATA

Energy consumption at set-point -80 °C (kWh/24h)	8,1
Average heat dissipation at set-point (-80°C, Amb. 20°C)(W)	340
Sound-pressure level [dB(A)]	47

LOAD-VARIANTS

Freezer racks per compartment	6
Cryoboxes, 50 mm	528

FEATURES

Alarm system, batterybacked	standard
Foam filled compartmen door	standard
Battery back-up system (CO2)	standard
Shipping pallet (extra specified pallet)	option(no additional article numbers; only on request)

FIXTURES

Shelves included/max. no. of shelves	3/13
--------------------------------------	------

ACCESSORIES

5m power cable	C 13 BS 1363 British plug – 5023-0287
	C 13 CEE 7/7 European plug – 5023-0285
	C 13 type 13 Swiss plug – 5023-0286
Deicing kit consisting of de-icing tray, wiper and scraper	8012-1900
Grid shelf – For temperature range -40 °C to -60 °C, 3 provided in set, including shelf supports	8012-1904
Shelf, Incl. shelf supports, stainless steel	8012-1902
WLAN kit, wireless connection between ULT units and APT-COM4, LIMS or customer solution.	8012-2262

STANDARDS & APPROVALS

Energy Star certified (3rd part)	yes
Machinery directive (EN ISO 12100, EN ISO 13732-3, EN60204-1)	yes
Applied voluntarily: EN61010-1, EN61010-2-11 (if wished, this could also be listed in the CE DoC)	yes
Electromagnetic Compability Directive 2014/30/EU (EN 61326-1)	yes
RoHS Directive (EN IEC 63000:2018)	yes
Compliant with DIN 13277	ULTs are validated referring to DIN DIN 12880; 2007-07

LABORATORY TEST MEASUREMENTS

Pull down	450 min
Noise level	47dBA
Warm-up time by power failure	250 min
Temperature variation	2,5 K
Temperaturre flucturation	1,5 K
Energy consumption	8,1 kW/24h




ULTF 700

ULT TECHNICAL SPECIFICATIONS

BIOMEDICAL

SELLING POINTS

Lowest energy consumption in its class	8,1
Environmentally-friendly refrigerants	R290/R170
Thermal insulation with unique long-life VIPs	vacuum insulation panels
Rust proof interior	Stainless steel 1.4016 grade
Individual safety concept	option
Temperature range [°C]	-90 °C to -40 °C
Compressor cooling	cascade
Innovative door gasket	reduce ice built-up
Detachable inner doors	stainless steel
Zero-voltage alarm contact	in-house alarm system
Internal data logger	USB read out
Ethernet interface	yes
Access ports	2x Ø28mm rear
Shipping pallet	without forklift
Packaging	Recyclable
Powder-coating	Solvent free



Products are subject to change due to enhancements and continuous development. Vestfrost Solutions reserve the right to alter any information, without further notice.



LABORATORY EQUIPMENT MAINTENANCE, REPAIR, CALIBRATION AND SALES

Established in 1987, Henderson Biomedical is the UK's leading laboratory equipment sales and service provider. Our knowledgeable team can provide you with excellent sales advice on a range of different types of laboratory equipment including centrifuges, refrigerators, freezers and heat sealers.

Henderson Biomedical is also able to provide you with first class after-sales service and calibration of your laboratory equipment. We are an **ISO 17025 (UKAS) accredited calibration test laboratory** and our team of Field Service Engineers cover the whole of the United Kingdom.

Please contact us for more information on the types of equipment we supply and the different after-sales services we can offer.

Henderson Biomedical

Unit 3, Swan Close
Croydon CR0 2DZ
United Kingdom

Tel: 020 8663 4610

For sales enquiries: sales@henderson-biomedical.co.uk
For all other enquiries: info@henderson-biomedical.co.uk
www.henderson-biomedical.co.uk

