BioCompact II 310





BioCompact II RR310. Drawers, reference container and glass door are optional extras.



The BioCompact II 310 models are available as refrigerator or freezer in either white or stainless steel finish. BioCompact II refrigerators can be equipped with a solid door with lock and self-closing system or glass door with LED light, lock and self-closing system.

 $\ensuremath{\mathsf{BioCompact}}$ II freezers are equipped with a solid door with lock and self-closing system.


The **BioCompact II 310** is an intermediate sized refrigerator or freezer cabinet with a small footprint, designed for a wide range of biostorage purposes where the prime focus is on dependability and exceptional performance.

The **BioCompact II 310** provides you with significantly better performance than any other cabinets in this segment, on account of a refrigeration system that does away with cold walls that can damage the contents and a unique air distribution system for storing ordinary biomaterial under consistent, stable conditions.

The design of the **BioCompact II 310** ensures you lots of ways to deal with individual storage needs, thanks to the versatile interior layout and a comprehensive selection of fixtures and fittings. The small footprint of this design also makes it the perfect biostorage unit for use in confined spaces.

The **BioCompact II 310** uses environmentally responsible HFC-free foam propellants and is available with HFC-free refrigerants. Based on decades of specialist know-how, these biostorage units are exceptionally energyefficient, and are the best performers on the market in relation to Scandinavian standards.

Available in either white or stainless steel finish, with a one-piece moulded ABS inner lining. Shelves and drawers are mounted in U-shaped rails moulded into the plastic walls.



Biostorage you can depend on

Version 03. Valid from 08.10.20



BioCompact II 310



Top panel with BioLine control unit

The MPC unit is specially developed for users of BioLine storage cabinets. Among its many features are acoustic temperature and door alarms, and a voltage-free connector (NC/NO) for remote alarms. The display can be locked.



Access port

24.5 mm port for ease of access, e.g. sensors for external temperature surveillance.



Extra sensor for providing a temperature reference within the storage compartment.



Using a refrigeration system based on a finned tube evaporator is unique for biostorage products in this segment, and provides unparalleled benefits. The design results in a refrigerated storage space with no cold walls that can damage any delicate items stored in the cabinet. This also makes it possible to ensure even better temperature stability inside the cabinet.





Shelves and drawers


A wide range of versatile interior fittings and layouts is available. The operating specifications and the interior layout can both be customised.



ATEX
All BioCompact II models
comply with ATEX Cat.3 Zone
2 requirements, both internal
and externally, allowing for
placement in locations where
explosive gas atmospheres
may be present.







AIR DISTRIBUTION

The unique Gram BioLine air distribution system makes sure the temperature inside the cabinet remains stable at all times. With the finned tube evaporator placed in the top, there are no cold walls inside the cabinet.

may be present.		
Technical specifications	BioCompact II RR310	BioCompact II RF310
Temperature range	+20/+2°C	-5/-25°C
Ambient temperature range	Solid door +10/+35 °C; glass door (RR) +10/+32 °C	
Control Unit	Gram Control Unit with voltage-free contact, E-sonsor, acoustic and visual door and temperature alarms that can be programmed individually, alarm recording and offset function	
Material interior Material exterior	ABS lining White lacquered steel or stainless steel finish	
Dimensions (W x D x H)	595 x 640 x 1190/1390	
Gross volume	218 litres/7.8 cubic feet	
Net weight	Unpacked net weight without optional fittings: 55 kg	
Net volume	189 litres/6.7 cubic feet	
Modules for shelves and drawers	14 shelves, 7 drawers, 4 wire baskets	
Insulation	50 mm polyurethane with HFC-free cyclopentane propellant	
K-value	Glass door 0 0.5061 W/m²K	Solid door 0.3550 W/m ² K
Refrigerant	R600a or R134a	
CO ₂ e	136	114
Refrigeration capacity at -10 °C	R600a 154 Watt / R134a 173 Watt	-
Refrigeration capacity at -25 °C	-	R600a 204 Watt / R134a 216 Watt
Energy consumption	0,63 kWh/24h	1,69 kWh/24h
Sound level	35,5 dB(A)	39,6 dB(A)
Base	Wheels/skids*	
Connection	230 V, 50 Hz	
Air system	Gram BioLine ventilated air distribution system	
Defrost system	Automatic smart defrost with re-evaporation of defrost water	

^{*} The cabinets can be delivered with castors or legs or prepared for mounting on a plinth as optional extras.

Gram Commercial // Aage Grams Vej 1 // DK-6500 Vojens // Denmark

Tel: +45 73 20 13 00 // Fax: +45 73 20 13 01 // info@gram-bioline.com // www.gram-bioline.com



LABORATORY EQUIPMENT MAINTENANCE, REPAIR, CALIBRATION AND SALES

Established in 1987, Henderson Biomedical is the UK's leading laboratory equipment sales and service provider. Our knowledgeable team can provide you with excellent sales advice on a range of different types of laboratory equipment including centrifuges, refrigerators, freezers and heat sealers.

Henderson Biomedical is also able to provide you with first class after-sales service and calibration of your laboratory equipment. We are an **ISO 17025 (UKAS) accredited calibration test laboratory** and our team of Field Service Engineers cover the whole of the United Kingdom.

Please contact us for more information on the types of equipment we supply and the different after-sales services we can offer.

Henderson Biomedical

Unit 3, Swan Close Croydon CRO 2DZ United Kingdom

Tel: 020 8663 4610

